

**Genetron 22 30lb/13.6kg Jug**

Version 2

Revision Date 10/01/2010

Print Date 12/01/2011

**SECTION 1. PRODUCT AND COMPANY IDENTIFICATION**

Product name : Genetron® 22  
MSDS Number : 00000009890  
Product Use Description : Refrigerant

Company : Honeywell International, Inc.  
101 Columbia Road  
Morristown, NJ 07962-1057

For more information call : 800-522-8001  
(Monday-Friday, 9:00am-5:00pm)

In case of emergency call : **Medical: 1-800-498-5701 or +1-651-523-0309**  
: **Transportation: 1-800-424-9300 or +1-703-527-3887**  
: (24 hours/day, 7 days/week)

**SECTION 2. HAZARDS IDENTIFICATION****Emergency Overview**

Form : Liquefied gas

Color : colourless

Odor : slight

Hazard Summary : Warning! Container under pressure. This product is not flammable at ambient temperatures and atmospheric pressure. Gas reduces oxygen available for breathing. Causes asphyxiation in high concentrations. The victim will not realize that he/she is suffocating. Inhalation may cause central nervous system effects. May cause cardiac arrhythmia. May cause drowsiness and dizziness. Do not breathe vapour. Irritating to eyes and skin. Avoid contact with skin, eyes and clothing. At higher temperatures, (>250°C), decomposition products may include hydrochloric acid (HCl), hydrofluoric acid (HF) and carbonyl halides. The ACGIH Threshold Limit Values (2007) for Hydrogen Fluoride are TLV-TWA 0.5 ppm and Ceiling Exposure Limit 2 ppm.

**Potential Health Effects**

Skin : Avoid skin contact with leaking liquid (danger of frostbite).  
May cause frostbite.  
Irritating to skin.

**Genetron 22 30lb/13.6kg Jug**

Version 2

Revision Date 10/01/2010

Print Date 12/01/2011

- Eyes : Causes serious eye irritation.  
May cause frostbite.
- Ingestion : Unlikely route of exposure.  
Effects due to ingestion may include:  
Gastrointestinal discomfort
- Inhalation : Gas reduces oxygen available for breathing.  
Causes asphyxiation in high concentrations. The victim will not realize that he/she is suffocating.  
Inhalation may cause central nervous system effects.  
May cause cardiac arrhythmia.  
Vapours may cause drowsiness and dizziness.
- Chronic Exposure : None known.

**Carcinogenicity**

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP, IARC, or OSHA.

**SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Formula : CHCIF2

Chemical Name	CAS-No.	Concentration
Chlorodifluoromethane	75-45-6	100.00%

**SECTION 4. FIRST AID MEASURES**

- Inhalation : Move to fresh air. If breathing is irregular or stopped, administer artificial respiration. Use oxygen as required, provided a qualified operator is present. Call a physician. Do not give drugs from adrenaline-ephedrine group.
- Skin contact : After contact with skin, wash immediately with plenty of water. If there is evidence of frostbite, bathe (do not rub) with lukewarm (not hot) water. If water is not available, cover with a clean, soft cloth or similar covering. If symptoms persist, call a physician.
- Eye contact : Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. In case of frostbite water should be lukewarm, not hot. If symptoms persist, call a physician.
- Ingestion : Unlikely route of exposure. As this product is a gas, refer to the

## Genetron 22 30lb/13.6kg Jug

Version 2

Revision Date 10/01/2010

Print Date 12/01/2011

inhalation section. Do not induce vomiting without medical advice. Call a physician immediately.

**Notes to physician**

Treatment : Because of the possible disturbances of cardiac rhythm, catecholamine drugs, such as epinephrine, should be used with special caution and only in situations of emergency life support. Treatment of overexposure should be directed at the control of symptoms and the clinical conditions. Treat frost-bitten areas as needed.

**SECTION 5. FIRE-FIGHTING MEASURES**

Flash point : not applicable

Lower explosion limit : None

Upper explosion limit : None

Suitable extinguishing media : The product is not flammable.  
ASHRAE 34  
Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.  
Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Specific hazards during fire fighting : Contents under pressure.  
This product is not flammable at ambient temperatures and atmospheric pressure.  
However, this material can ignite when mixed with air under pressure and exposed to strong ignition sources.  
Container may rupture on heating.  
Cool closed containers exposed to fire with water spray.  
Do not allow run-off from fire fighting to enter drains or water courses.  
Vapours are heavier than air and can cause suffocation by reducing oxygen available for breathing.  
In case of fire hazardous decomposition products may be produced such as:  
Gaseous hydrogen chloride (HCl).  
Hydrogen fluoride  
Carbon monoxide  
Carbon dioxide (CO<sub>2</sub>)  
Carbonyl halides

Special protective equipment for fire-fighters : In the event of fire and/or explosion do not breathe fumes.  
Wear self-contained breathing apparatus and protective suit.

**Genetron 22 30lb/13.6kg Jug**

Version 2

Revision Date 10/01/2010

Print Date 12/01/2011

No unprotected exposed skin areas.

**SECTION 6. ACCIDENTAL RELEASE MEASURES**

- Personal precautions** : Immediately evacuate personnel to safe areas.  
Keep people away from and upwind of spill/leak.  
Wear personal protective equipment. Unprotected persons must be kept away.  
Remove all sources of ignition.  
Avoid skin contact with leaking liquid (danger of frostbite).  
Ventilate the area.  
After release, disperses into the air.  
Vapours are heavier than air and can cause suffocation by reducing oxygen available for breathing.  
Avoid accumulation of vapours in low areas.  
Unprotected personnel should not return until air has been tested and determined safe.  
Ensure that the oxygen content is  $\geq 19.5\%$ .
- Environmental precautions** : Prevent further leakage or spillage if safe to do so.  
The product evaporates readily.
- Methods for cleaning up** : Ventilate the area.

**SECTION 7. HANDLING AND STORAGE****Handling**

- Handling** : Handle with care.  
Avoid inhalation of vapour or mist.  
Do not get in eyes, on skin, or on clothing.  
Wear personal protective equipment.  
Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50 °C.  
Follow all standard safety precautions for handling and use of compressed gas cylinders.  
Use authorized cylinders only.  
Protect cylinders from physical damage.  
Do not puncture or drop cylinders, expose them to open flame or excessive heat.  
Do not pierce or burn, even after use. Do not spray on a naked flame or any incandescent material.  
Do not remove screw cap until immediately ready for use.  
Always replace cap after use.
- Advice on protection against fire and explosion** : The product is not flammable.  
Can form a combustible mixture with air at pressures above atmospheric pressure.

**Genetron 22 30lb/13.6kg Jug**

Version 2

Revision Date 10/01/2010

Print Date 12/01/2011

**Storage**

Requirements for storage areas and containers : Pressurized container: Protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use.  
Keep containers tightly closed in a dry, cool and well-ventilated place.  
Storage rooms must be properly ventilated.  
Ensure adequate ventilation, especially in confined areas.  
Protect cylinders from physical damage.

**SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

- Protective measures : Do not breathe vapour.  
Avoid contact with skin, eyes and clothing.  
Ensure that eyewash stations and safety showers are close to the workstation location.
- Engineering measures : General room ventilation is adequate for storage and handling.  
Perform filling operations only at stations with exhaust ventilation facilities.
- Eye protection : Wear as appropriate:  
Safety glasses with side-shields  
If splashes are likely to occur, wear:  
Goggles or face shield, giving complete protection to eyes
- Hand protection : Leather gloves  
In case of contact through splashing:  
Protective gloves  
Neoprene gloves  
Polyvinyl alcohol or nitrile- butyl-rubber gloves
- Skin and body protection : Avoid skin contact with leaking liquid (danger of frostbite).  
Wear cold insulating gloves/face shield/eye protection.
- Respiratory protection : In case of insufficient ventilation wear suitable respiratory equipment.  
Wear a positive-pressure supplied-air respirator.  
Vapours are heavier than air and can cause suffocation by reducing oxygen available for breathing.  
For rescue and maintenance work in storage tanks use self-contained breathing apparatus.
- Hygiene measures : Handle in accordance with good industrial hygiene and safety practice.  
Ensure adequate ventilation, especially in confined areas.

## Genetron 22 30lb/13.6kg Jug

Version 2

Revision Date 10/01/2010

Print Date 12/01/2011

Avoid contact with skin, eyes and clothing.  
Remove and wash contaminated clothing before re-use.  
Keep working clothes separately.

**Exposure Guidelines**

Chlorodifluoromethane	75-45-6	ACGIH	TWA		1,000 ppm
		NIOSH	STEL	1,250 ppm	4,375 mg/m3
		NIOSH	REL	1,000 ppm	3,500 mg/m3
		OSHA Z1A	TWA	1,000 ppm	3,500 mg/m3

**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Form	: Liquefied gas
Color	: colourless
Odor	: slight
Molecular Weight	: 86.46 g/mol
pH	: neutral
Melting point/range	: -160 °C (-256 °F)
Boiling point/boiling range	: -40.8 °C (-41.4 °F)
Vapor pressure	: 9,384 hPa at 21.1 °C (70.0 °F)
Vapor pressure	: 21,470 hPa at 54.4 °C (129.9 °F)
Relative vapour density	: 3 (Air = 1.0)
Density	: 1.21 g/cm3 at 21.1 °C (70.0 °F)
Water solubility	: 3.0 g/l
Partition coefficient: n-octanol/water	: log Pow: 1.08 - 1.13  The product is more soluble in octanol.

**Genetron 22 30lb/13.6kg Jug**

Version 2

Revision Date 10/01/2010

Print Date 12/01/2011

**SECTION 10. STABILITY AND REACTIVITY**

- Conditions to avoid : Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50 °C.  
Decomposes under high temperature.  
Some risk may be expected of corrosive and toxic decomposition products.  
Can form a combustible mixture with air at pressures above atmospheric pressure.  
Do not mix with oxygen or air above atmospheric pressure.
- Materials to avoid : Finely divided aluminium  
Potassium  
Calcium  
Powdered metals  
Aluminium  
Magnesium  
Zinc
- Hazardous decomposition products : In case of fire hazardous decomposition products may be produced such as:  
Gaseous hydrogen chloride (HCl).  
Gaseous hydrogen fluoride (HF).  
Carbonyl halides  
Carbon monoxide  
Carbon dioxide (CO<sub>2</sub>)
- Thermal decomposition : >250 °C
- Hazardous reactions : Hazardous polymerisation does not occur.  
Stable under normal conditions.

**SECTION 11. TOXICOLOGICAL INFORMATION**

- Acute inhalation toxicity : LC50: > 300000 ppm  
Exposure time: 4 h  
Species: rat
- Repeated dose toxicity : Species: rat  
Application Route: Inhalation  
Exposure time: Lifetime Exposure  
NOEL: 10000 ppm  
Note: Lifetime exposure of male rats was associated with a small increase in salivary gland fibrosarcomas.

**Genetron 22 30lb/13.6kg Jug**

Version 2

Revision Date 10/01/2010

Print Date 12/01/2011

Further information : Acute toxicity Chlorodifluoromethane (HCFC-22): Cardiac sensitisation threshold (dog): 50000 ppm. Rapid evaporation of the liquid may cause frostbite. Vapours are heavier than air and can cause suffocation by reducing oxygen available for breathing. May cause cardiac arrhythmia.

**SECTION 12. ECOLOGICAL INFORMATION****Ecotoxicity effects**

Toxicity to fish : static test  
LC50: 777 mg/l  
Exposure time: 96 h  
Species: Danio rerio (zebra fish)

Toxicity to daphnia and other aquatic invertebrates. : static test  
EC50: 433 mg/l  
Exposure time: 48 h  
Species: Daphnia magna (Water flea)

**Further information on ecology**

Additional ecological information : Accumulation in aquatic organisms is unlikely. This product contains greenhouse gases which may contribute to global warming. Do NOT vent to the atmosphere. To comply with provisions of the U.S. Clean Air Act, any residual must be recovered. This product is subject to U.S. Environmental Protection Agency Clean Air Act Regulations at 40 CFR Part 82. Section 611 requires the following label text on all shipments of this product:  
Warning: Contains Chlorodifluoromethane (HCFC-22), a substance which harms public health and environment by destroying ozone in the upper atmosphere. Refer to sections 610 and 612 for list of acceptable and unacceptable uses for this product.

**SECTION 13. DISPOSAL CONSIDERATIONS**

Waste Information: Observe all Federal, State, and Local Environmental regulations.  
Additional advice : This product is subject to U.S. Environmental Protection Agency Clean Air Act Regulations Section 608 in 40 CFR Part 82



**Genetron 22 30lb/13.6kg Jug**

Version 2

Revision Date 10/01/2010

Print Date 12/01/2011

regarding refrigerant recycling.

**SECTION 14. TRANSPORT INFORMATION**

<b>DOT</b>	UN/ID No.	: UN 1018
	Proper shipping name	: CHLORODIFLUOROMETHANE
	Class	: 2.2
	Packing group	
	Hazard Labels	: 2.2
<b>IATA</b>	UN/ID No.	: UN 1018
	Description of the goods	: CHLORODIFLUOROMETHANE
	Class	: 2.2
	Hazard Labels	: 2.2
	Packing instruction (cargo aircraft)	: 200
	Packing instruction (passenger aircraft)	: 200
<b>IMDG</b>	UN/ID No.	: UN 1018
	Description of the goods	: CHLORODIFLUOROMETHANE
	Class	: 2.2
	Hazard Labels	: 2.2
	EmS Number	: F-C
	Marine pollutant	: no

**SECTION 15. REGULATORY INFORMATION****Inventories**

1907/2006 (EU)	: This mixture contains only ingredients which have been subject to a pre-registration according to Regulation (EC) No. 1907/2006 (REACH).
US. Toxic Substances Control Act	: On TSCA Inventory
Australia. Industrial Chemical (Notification and Assessment) Act	: On the inventory, or in compliance with the inventory
Canada. Canadian Environmental Protection Act (CEPA). Domestic Substances List (DSL). (Can. Gaz. Part II, Vol. 133)	: All components of this product are on the Canadian DSL list.

**Genetron 22 30lb/13.6kg Jug**

Version 2

Revision Date 10/01/2010

Print Date 12/01/2011

Japan. Kashin-Hou Law List : On the inventory, or in compliance with the inventory

Korea. Toxic Chemical Control Law (TCCL) List : On the inventory, or in compliance with the inventory

Philippines. The Toxic Substances and Hazardous and Nuclear Waste Control Act : On the inventory, or in compliance with the inventory

China. Inventory of Existing Chemical Substances : On the inventory, or in compliance with the inventory

NZIOC - New Zealand : On the inventory, or in compliance with the inventory

**National regulatory information**

**SARA 313 Components** : Chlorodifluoromethane 75-45-6

**SARA 311/312 Hazards** : Acute Health Hazard  
Sudden Release of Pressure Hazard

**California Prop. 65** : This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

**Massachusetts RTK** : Chlorodifluoromethane 75-45-6

**New Jersey RTK** : Chlorodifluoromethane 75-45-6

**Pennsylvania RTK** : Chlorodifluoromethane 75-45-6

**WHMIS Classification** : A  
This product has been classified according to the hazard criteria of the CPR and the MSDS contains all of the information required by the CPR.

**Global warming potential** : 1,500

**Ozone depletion potential** : 0.06

**Genetron 22 30lb/13.6kg Jug**

Version 2

Revision Date 10/01/2010

Print Date 12/01/2011

(ODP)

**SECTION 16. OTHER INFORMATION**

	<b>HMIS III</b>	<b>NFPA</b>
Health hazard	: 1	2
Flammability	: 1	1
Physical Hazard	: 0	
Instability	:	0