

SEL00375 (OBSOLETE) 793  
 SEL00376  
 SEL00489

LOCTITE CORPORATION

1001 TROUT BROOK CROSSING  
 ROCKY HILL, CT 06067-3910  
 EMERGENCY PHONE: (860) 571-5100

ISSUED 6/21/00  
 11:56:59  
 FAX: (860) 571-5465

REC'D JUN 26 2000

MATERIAL SAFETY DATA SHEET

Page 1 of 3

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Name: Gasket Eliminator(R) 515 Sealant  
 Item No.: 51580  
 Part No.: 51574  
 Product Type: Anaerobic

2. COMPOSITION, INFORMATION ON INGREDIENTS

Ingredients	CAS No.	%
Polyurethane methacrylate	Proprietary	70-75
Polyglycol dimethacrylate	25852-47-5	10-15
ACRYLIC ACID*	79-10-7	5-7
CUMENE HYDROPEROXIDE*	80-15-9	3-5
SILICA, AMORPHOUS, FUMED, CRYSTALLINE-FREE	112945-52-5	3-5
SACCHARIN	81-07-2	1-3
1-Acetyl-2-phenylhydrazine	114-83-0	0.1-1

\* This component is listed as a SARA Section 313 Toxic Chemical.

The polyurethane methacrylate resin is registered with the state of New Jersey as a trade secret: NJ TSNR 06-070-1067-5073P.

Ingredients which have exposure limits

Exposure Limits (TWA) Ingredients	ACGIH (TLV)	OSHA (PEL)	OTHER
ACRYLIC ACID	2 ppm TWA skin	10 ppm TWA skin	1 ppm TWA skin
CUMENE HYDROPEROXIDE	5.9 mg/m3 skin	30 mg/m3 skin	3 ppm STEL skin
	None	None	1ppm (6mg/m3) Skin(WHEEL)
SILICA, AMORPHOUS, FUMED, CRYSTALLINE-FREE	10 mg/m3 TWA	6 mg/m3 TWA	3 mg/m3 TWA resp. dust

  

Exposure Limits (STEL) Ingredients	ACGIH (TLV)	OSHA (PEL)

3. HAZARDS IDENTIFICATION

Toxicity: Liquid is an eye and skin irritant.  
 Vapors may irritate eye, nose and throat.  
 Estimated oral LD50 more than 5000 mg/kg.  
 Estimated dermal LD50 more than 2000 mg/kg.

Primary Routes of Entry: None known

Signs and Symptoms of Exposure: Irritation of eyes, skin, nose or throat. May cause dermatitis on prolonged contact in sensitive individuals.

Existing Conditions Aggravated by Exposure: Acrylic acid: Upper respiratory and lung diseases, dermatitis

Ingredients	Literature Referenced Target Organ and Other Health Effects	Carcinogen		
		NTP	IARC	OSHA
Polyurethane methacrylate	No Data	NO	NO	NO
Polyglycol dimethacrylate	ALG IRR	NO	NO	NO
ACRYLIC ACID	ALG COR IRR KID LIV	NO	N/A	NO
CUMENE HYDROPEROXIDE	ALG CNS COR IRR MUT	NO	NO	NO
SILICA, AMORPHOUS, FUMED, CRYSTALLINE-FREE	NUI	NO	N/A	NO
SACCHARIN	NTO	NO	2B	NO
1-Acetyl-2-phenylhydrazine	ALG BLO KID MUT SOM	NO	NO	NO

Abbreviations

N/A Not Applicable	2B Possibly carcinogenic to humans
ALG Allergen	BLO Blood
CNS Central nervous system	COR Corrosive
IRR Irritant	KID Kidney
LIV Liver	MUT Mutagen
NTO No Target Organs	NUI Nuisance dust
SOM Evidence of some carcinogenicity	

793

LOCTITE CORPORATION

1001 TROUT BROOK CROSSING  
ROCKY HILL, CT 06067-3910  
EMERGENCY PHONE: (860) 571-5100

ISSUED 6/21/00  
11:56:59  
FAX: (860) 571-5465

MATERIAL SAFETY DATA SHEET

Page 2 of 3

Product Name: Gasket Eliminator(R) 515 Sealant  
Item No.: 51580

4. FIRST AID MEASURES

Ingestion: Do not induce vomiting. Keep individual calm. Obtain medical attention.  
Inhalation: Remove to fresh air. If symptoms persist, obtain medical attention.  
Skin Contact: Flush thoroughly with water.  
Eye Contact: Flush at least 15 minutes with water. Obtain medical attention.

5. FIRE FIGHTING MEASURES

Flash Point: More than 200°F Method: Tag Closed Cup  
Recommended  
Extinguishing Agents: Carbon dioxide, foam, dry chemical  
Special Firefighting Procedures: Not available  
Hazardous Products formed by Fire or Thermal Decomposition: Irritating organic vapors  
Unusual Fire or Explosion Hazards: None  
Explosive Limits:  
(% by volume in air) Lower 2.0% Acrylic acid  
(% by volume in air) Upper 8.0% Acrylic acid

6. ACCIDENTAL RELEASE MEASURES

Steps to be taken in case of spill or leak: Soak up in an inert absorbent. Store in partly filled, closed container until disposal.

7. HANDLING AND STORAGE

Safe Storage: Store below 100°F  
(Contact Loctite Customer Service 1-800-243-4874 for shelf life information)  
Handling: Avoid prolonged skin contact. Keep away from eyes. Avoid prolonged breathing of vapors.

8. EXPOSURE CONTROLS, PERSONAL PROTECTION

Eyes: Safety glasses or goggles.  
Skin: Rubber or plastic gloves.  
Ventilation: Sufficient to maintain vapor concentration below TLV.  
Respiratory: Not available  
See Section 2 for Exposure Limits.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Purple Gel  
Odor: Sharp, Irritating  
Boiling Point: More than 300°F  
pH: Does not apply  
Solubility in Water: Slight  
Specific Gravity: 1.1 at 80°F  
Volatile Organic Compound (EPA Method 24): 12.8%; 141 grams per liter  
Vapor Pressure: Less than 10mm at 80°F  
Vapor Density: Not available  
Evaporation Rate (Ether = 1): Not available

10. STABILITY AND REACTIVITY

Stability: Stable  
Hazardous Polymerization: Will not occur  
Incompatibility: None  
Conditions to Avoid: Not available  
Hazardous Decomposition Products (non-thermal): None

11. TOXICOLOGICAL INFORMATION

See Section 3.

12. ECOLOGICAL INFORMATION

No data available

793

LOCTITE CORPORATION

1001 TROUT BROOK CROSSING  
ROCKY HILL, CT 06067-3910  
EMERGENCY PHONE: (860) 571-5100

ISSUED 6/21/00  
11:56:59  
FAX: (860) 571-5465

MATERIAL SAFETY DATA SHEET

Page 3 of 3

Product Name: Gasket Eliminator(R) 515 Sealant  
Item No.: 51580

13. DISPOSAL CONSIDERATIONS

Recommended methods of disposal: Incinerate following EPA and local regulations.  
EPA Hazardous Waste Number: NH - Not a RCRA Hazardous Waste Material

14. TRANSPORTATION INFORMATION

DOT (49 CFR 172)  
Domestic Ground Transport  
Proper Shipping Name: Unrestricted  
Hazard Class or Division: Unrestricted  
Identification Number: None  
Marine Pollutant: None  
IATA  
Proper Shipping Name: Unrestricted  
Class or Division: Unrestricted  
UN or ID Number: None

15. REGULATORY INFORMATION

CA Proposition 65: WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.  
Ethylene Oxide  
  
This product contains Saccharin. No Prop65 hazard warning is necessary if this product is used as reasonably anticipated.

16. OTHER INFORMATION

Estimated NFPA(R) Code:  
Health Hazard: 2  
Fire Hazard: 1  
Reactivity Hazard: 1  
Specific Hazard: Does not apply  
  
Estimated HMIS(R) Code:  
Health Hazard: 2  
Flammability Hazard: 1  
Reactivity Hazards: 1  
Personal Protection: See Section 8.

NFPA is a registered trademark of the National Fire Protection Assn.  
HMIS is a registered trademark of the National Paint and Coatings Assn.

Prepared By: Stephen Repetto  
Title: Research Chemist, Environmental Health & Safety  
Company: Loctite Corp., 1001 Tr Br Cr, Rocky Hill CT 06067  
(24hr.) Phone: (860) 571-5100  
Revision Date: January 26, 1999 Revision: 0036