

REC'D FEB 25 2000

MATERIAL SAFETY DATA SHEET- RectorSeal® T PLUS 2®

5965

SLT00015
SLT00016
SLT00034

MSDS0077

Ver. No.1

Ver. Date April 14, 1999

SECTION 1 CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: RectorSeal® T Plus 2®
PRODUCT CODES: 23710, 23631, 23551, 23431, 23391, 23271, 23191, 23112
CHEMICAL FAMILY: Organic
USE: Pipe Thread Sealing Compound
MANUFACTURE / SUPPLIER
RectorSeal
2601 Spenwick
Houston, Texas 77055 USA

EMERGENCY TELEPHONE NUMBERS:

Chemtrec 24 hours: (800) 424-9300
RectorSeal: (713) 263-8001

NON EMERGENCY TELEPHONE NUMBERS:

Technical Service: (800) 231-3345

SECTION 2 COMPOSITION / INFORMATION ON INGREDIENTS

HAZARDOUS COMPONENTS	CAS NO.	APPROX	OSHA PEL	ACGIH TLV	OTHER LIMITS	HMIS	NFPA
		%					

None as defined by OSHA Hazardous Communication Standard 29 CFR 1910.1200.

SECTION 3 HAZARDS IDENTIFICATION

SUMMARY OF ACUTE HAZARDS May produce slight to moderate skin and eye irritation.

<u>ROUTE OF EXPOSURE</u>	<u>SIGNS AND SYMPTOMS</u>	<u>PRIMARY ROUTE(S)</u>
INHALATION:	Inhalation of thermal decomposition byproducts from burning may cause "polymer fume fever" characterized by fever, cough, malaise.	No
EYE CONTACT:	Irritation, watering may occur.	Yes
SKIN CONTACT:	Frequent or prolonged contact may irritate and cause dermatitis.	Yes
INGESTION:	May cause nausea and vomiting. Not expected to produce toxic effects unless large amounts are ingested.	No

SUMMARY OF CHRONIC HAZARDS: Chronic effects are N/D.
MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: N/D

SECTION 4 FIRST AID MEASURES

INHALATION: If overcome by exposure, remove victim to fresh air immediately. Give oxygen or artificial respiration as needed. Obtain emergency medical attention. Prompt action is essential.
EYE CONTACT: Immediately flush with large amounts of water for at least 15 minutes. Get prompt medical attention.
SKIN CONTACT: Wash with soap and water. Remove contaminated clothing. If irritation occurs, seek medical attention.
INGESTION: If swallowed, call a physician immediately. Only induce vomiting at the instruction of a physician. Never give anything by mouth to an unconscious person.

SECTION 5 FIRE FIGHTING MEASURES

FLASH POINT: >300°F (149°C) SETA CC **FLAMMABILITY LIMITS:** LEL: N/D UEL: N/D
EXTINGUISHING MEDIA: Foam, dry chemical, carbon dioxide or water fog.
SPECIAL FIRE FIGHTING PROCEDURES: Wear self-contained full face piece breathing apparatus and other protective clothing. Evacuate area. Hazardous decomposition products possible (see Section 10).
UNUSUAL FIRE AND EXPLOSION HAZARDS: Heat may build up pressure and rupture closed containers. Above 500°F (260°C) the fumes are acutely toxic.

SECTION 6 ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Remove all sources of ignition. Wipe up spills to prevent footing hazard. Avoid flushing into sewers, drains, waterways and soil. Wear protective clothing.

SECTION 7 STORAGE AND HANDLING

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: Keep container closed when not in use. Do not store near heat, sparks, or open flames.
OTHER PRECAUTIONS: Avoid prolonged or repeated contact with skin or clothing. Empty containers may contain residues and vapors; treat as if full and observe all products precautions. Do not reuse empty containers. **KEEP OUT OF REACH OF CHILDREN.**

