

REC'D JUL 28 1997

MATERIAL SAFETY DATA SHEET

3099

SECTION 1 — PRODUCT IDENTIFICATION AND USE

PRODUCT IDENTIFIER SERVICE FIRST CORK TAPE		PRODUCT IDENTIFICATION NUMBER (PIN) TAP0025	
PRODUCT USE Insulate hot or cold surfaces to stop drips & condensation from pipes & tubes.			
MANUFACTURER'S NAME SOLD BY: North American Research Corporation		SUPPLIER'S NAME The Trane Company	
STREET ADDRESS P.O. Box 1318		STREET ADDRESS 3600 Pammel Creek Road	
CITY Lewisville	PROVINCE Texas	CITY La Crosse	PROVINCE Wisconsin
POSTAL CODE 75067	EMERGENCY TELEPHONE NO. 800-527-7520	POSTAL CODE 54601	EMERGENCY TELEPHONE NO. 800-424-9300

SECTION 2 — HAZARDOUS INGREDIENTS

HAZARDOUS INGREDIENTS	%	CAS NUMBER	LD ₅₀ OF INGREDIENT (SPECIFY SPECIES AND ROUTE)	LC ₅₀ OF INGREDIENT (SPECIFY SPECIES)
Asphalt (fumes only)	N/A	8052-42-4	N/A	N/A
NFPA RATING				
"0" Health				
"0" Fire				
"0" Reactivity				

SECTION 3 — PHYSICAL DATA

PHYSICAL STATE Solid	ODOUR AND APPEARANCE Rough, black tape; Slight odor of asphalt			ODOUR THRESHOLD (ppm) N/A
VAPOUR PRESSURE (mm Hg) N/A	VAPOUR DENSITY (AIR=1) N/A	EVAPORATION RATE N/A	BOILING POINT (°C) N/A	FREEZING POINT (°C) N/A
pH N/A	SPECIFIC GRAVITY 0.7	COEFF. WATER/OIL DIST. N/A		

SECTION 4 — FIRE AND EXPLOSION DATA

FLAMMABILITY YES <input type="checkbox"/> NO <input checked="" type="checkbox"/> IF YES, UNDER WHICH CONDITIONS?		
MEANS OF EXTINCTION Dry chemical, carbon dioxide, foam		
FLASHPOINT (°C) AND METHOD Greater than 500°F, COC	UPPER FLAMMABLE LIMIT (% BY VOLUME) N/A	LOWER FLAMMABLE LIMIT (% BY VOLUME) N/A
AUTOIGNITION TEMPERATURE (°C) N/A	HAZARDOUS COMBUSTION PRODUCTS None	
EXPLOSION DATA	SENSITIVITY TO IMPACT N/A	SENSITIVITY TO STATIC DISCHARGE N/A

SECTION 5 — REACTIVITY DATA

CHEMICAL STABILITY YES <input checked="" type="checkbox"/> NO <input type="checkbox"/> IF NO, UNDER WHICH CONDITIONS?	
INCOMPATIBILITY WITH OTHER SUBSTANCES YES <input checked="" type="checkbox"/> NO <input type="checkbox"/> IF SO, WHICH ONES? Strong oxidizers	
REACTIVITY, AND UNDER WHAT CONDITIONS N/A	
HAZARDOUS DECOMPOSITION PRODUCTS Carbon dioxide, carbon monoxide and hydrogen sulfide	

3099

PRODUCT IDENTIFIER

CORK TAPE

SECTION 6 — TOXICOLOGICAL PROPERTIES

ROUTE OF ENTRY

SKIN CONTACT

SKIN ABSORPTION

EYE CONTACT

INHALATION

INGESTION

EFFECTS OF ACUTE EXPOSURE TO PRODUCT

Prolonged or repeated skin contact may result in irritation or dermatitis.

EFFECTS OF CHRONIC EXPOSURE TO PRODUCT: Prolonged or repeated skin contact may result in skin irritation or dermatitis. Asphalt contains a small amount of polycyclic aromatic hydrocarbons.

EXPOSURE LIMITS ACGIH TLV= 5mg/m ³	IRRITANCY OF PRODUCT Dryness & irritation to skin	SENSITIZATION TO PRODUCT N/A	CARCINOGENICITY IARC Monographs= Animals (2B)
TERATOGENICITY N/A	REPRODUCTIVE TOXICITY N/A	MUTAGENICITY N/A	SYNERGISTIC PRODUCTS N/A

SECTION 7 — PREVENTIVE MEASURES

PERSONAL PROTECTIVE EQUIPMENT:

GLOVES (SPECIFY) None	RESPIRATOR (SPECIFY) None	EYE (SPECIFY) None
FOOTWEAR (SPECIFY) None	CLOTHING (SPECIFY) None	OTHER (SPECIFY) None

ENGINEERING CONTROLS (SPECIFY, EG. VENTILATION, ENCLOSED PROCESS.)

N/A

LEAK AND SPILL PROCEDURE

Not applicable This material is not regulated

WASTE DISPOSAL: Dispose of in accordance with federal, state & local regulations as a solid waste. This material is not regulated under "RCRA" hazardous waste, but may be regulated under state & local regulations.

HANDLING PROCEDURES AND EQUIPMENT

Do not store near strong oxidizers or open flame.

STORAGE REQUIREMENTS

KEEP OUT OF REACH OF CHILDREN.

SPECIAL SHIPPING INFORMATION

Sealing Compounds NMFC#42030

SECTION 8 — FIRST AID MEASURES

SPECIFIC MEASURES

Wash skin with plenty of water.

SECTION 9 — PREPARATION DATE OF MSDS

PREPARED BY (GROUP, DEPARTMENT, ETC.)

Kelvin Cook

PHONE NUMBER

(972) 492-1800

DATE

7/8/97