

REC'D SEP 07 1999

6127

MSDS #N117

Material Safety Data Sheet

May be used to comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200. Standard must be consulted for specific requirements.

U.S. Department of Labor

Occupational Safety and Health Administration
(Non-Mandatory Form)
Form Approved

OMB No. 1218-0072 **TAP00048**
X21130655-010



IDENTITY (As Used on Label and List)
HYDRO-BALANCE CORK INSULATION TAPE

Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.

Section I

#H-2700

Manufacturer's Name Q'SO Incorporated	Emergency Telephone Number During Transit-INFOTRAC (972) 492-1800 800-535-5053
Address (Number, Street, City, State, and ZIP Code) P.O. Box 79680	Telephone Number for Information (972) 492-1800
Saginaw, TX 76179	Date Prepared 9/2/97
(Packaged by North American Research Corp)	Signature of Preparer (optional) <i>Robin Cook</i>

Section II — Hazardous Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity; Common Name(s))	OSHA PEL	ACGIH TLV	Other Limits Recommended	% (optional)
Asphalt (fumes only) (CAS #8052-42-4)	N/A	Molten State 5mg/M	N/A	N/A

NFPA HAZARD RATING:

"0" Health
"0" Flammable
"0" Reactive

SHIPPING DESCRIPTION:

Sealing Compounds NMFC#42030

Based on data available, none of the components in this product are considered to be hazardous according to OSHA Hazard Communication Standard 29CFR1910.1200 when used as a solid.

Section III — Physical/Chemical Characteristics

Boiling Point	N/A	Specific Gravity (H ₂ O = 1)	0.7
Vapor Pressure (mm Hg.)	N/A	Melting Point	N/A
Vapor Density (AIR = 1)	N/A	Evaporation Rate (Butyl Acetate = 1)	N/A
Solubility in Water	Insoluble		
Appearance and Odor	Rough, black tape; Slight odor of asphalt		

Section IV — Fire and Explosion Hazard Data

Flash Point (Method Used) Pensky Marten closed cup >390°F	Flammable Limits	LEL N/A	UEL N/A
Extinguishing Media Dry chemical, carbon dioxide, foam			
Special Fire Fighting Procedures Do not use water, material will float			

Unusual Fire and Explosion Hazards
None

6127

Section V — Reactivity Data

Stability	Unstable		Conditions to Avoid None
	Stable	X	

Incompatibility (Materials to Avoid) Strong oxidizers

Hazardous Decomposition or Byproducts
Carbon dioxide, carbon monoxide and hydrogen sulfide

Hazardous Polymerization	May Occur		Conditions to Avoid None
	Will Not Occur	X	

Section VI — Health Hazard Data

Route(s) of Entry: Inhalation? No Skin? X Ingestion? No

Health Hazards (Acute and Chronic)
Prolonged or repeated skin contact may result in skin irritation or dermatitis.

Carcinogenicity: NTP? No IARC Monographs? Yes-animals (2B) OSHA Regulated? No

IARC classified asphalt as a Group 3 material.

Signs and Symptoms of Exposure Dryness and irritation to the skin

Medical Conditions Generally Aggravated by Exposure Dermatitis

Emergency and First Aid Procedures
Wash skin with soap and water for skin contact. Flush eye with water for eye contact.

If any irritation persist, consult a physician.

Section VII — Precautions for Safe Handling and Use

Steps to Be Taken in Case Material Is Released or Spilled Not applicable.

Waste Disposal Method
This material is not regulated under the "RCRA" hazardous waste regulations, but may be under state and local regulations.

Precautions to Be Taken in Handling and Storing
Do not store near open flame. Avoid unnecessary exposure to skin contact.

Other Precautions
Keep out of reach of children. Read label before using.

Section VIII — Control Measures

Respiratory Protection (Specify Type)
Not required

Ventilation	Local Exhaust	N/A	Special	N/A
	Mechanical (General)	N/A	Other	N/A

Protective Gloves Not required Eye Protection Not required

Other Protective Clothing or Equipment Not required

Work/Hygienic Practices
Wash hands after use & before eating, drinking or using washroom.