

REC'D FEB 24 2000

6109  
TOL00416

MATERIAL SAFETY DATA SHEET  
29 CFR 1910.1200 OSHA Hazard  
Communication Rule Format  
Chem-Tel 24 Hour Emergency # 1-800-255-3924

MINE SAFETY APPLIANCES COMPANY  
P.O. Box 426  
Pittsburgh, PA 15230  
PHONE (412) 967-3000

This product contains nitrogen, a substance subject to the Pennsylvania Worker and Community Right-To-Know Act.

---

**PRODUCT IDENTITY**

---

LABEL IDENTITY - MSA P/N 711474 Calibration Check Gas, 50 ppm R - 123 in Nitrogen  
CHEMICAL NAME - 2,2 - Dichloro - 1,1,1 - Trifluoroethane in Nitrogen  
ADDITIONAL IDENTITIES - MSA P/N 711474 Calibration Gas 50 ppm HCFC - 123 in Nitrogen  
FORMULA -  $\text{CHCl}_2\text{CF}_3$  in  $\text{N}_2$

---

**APPLICABLE CHEMICAL CONTENTS**

---

	<u>%</u>	<u>TWA</u>
$\text{CHCl}_2\text{CF}_3$ (CAS 306-83-2)	0.005	None established*
Nitrogen (CAS 7727-37-9)	Balance	None

\*A manufacturer suggests 10 ppm TWA

NOTE: Gas Under Pressure, 1000 PSIG at 70°F, Approx. 100 Liters Gas at Atmospheric Pressure

---

**PHYSICAL AND CHEMICAL PROPERTIES**

---

APPEARANCE AND ODOR - Colorless, Odorless Gas Mixture  
BOILING POINT - N/A  
VAPOR PRESSURE - N/A  
VAPOR DENSITY (AIR = 1) - > 1  
SOLUBILITY IN WATER -  $\text{CHCl}_2\text{CF}_3$  - approx. 62 cm<sup>3</sup>/100 ml (25°C)  
Nitrogen - 2.3 cm<sup>3</sup>/100 ml (0°C)  
SPECIFIC GRAVITY (H<sub>2</sub>O = 1) - N/A  
PERCENT VOLATILE BY VOLUME - N/A

N/A - Not Applicable

---

**PHYSICAL HAZARD INFORMATION**

---

PHYSICAL HAZARD - Compressed Gas, 1000 PSIG at 70°F

CONDITIONS OR MATERIALS TO AVOID - Avoid bases. Avoid powdered active metals such as aluminum, alkali metals or alkaline earth metals.

FLASH POINT - N/A

EXTINGUISHING MEDIA - This Calibration Gas Mixture Is Not Flammable

SPECIAL FIRE FIGHTING PROCEDURES -  $\text{CHCl}_2\text{CF}_3$  decomposes at high temperatures yielding toxic halogen compounds. Use self-contained pressure demand type breathing apparatus with full facepiece.

UNUSUAL FIRE AND EXPLOSION HAZARDS - Gas Under Pressure, 1000 PSIG at 70°F. Do Not Exceed 120°F.

6109

MSA P/N 711474

---

### HEALTH HAZARDS

---

HEALTH HAZARDS - No TWA has been established for  $\text{CHCl}_2\text{CF}_3$ . A manufacturer suggests 10 ppm TWA. Inhalation 4-hour LC50 (Rat) is 32,000 ppm. Skin absorption LD50 (Rabbit) is >2000 mg/kg. Nitrogen is an asphyxiant.

SIGNS AND SYMPTOMS OF EXPOSURE: None known for 50 ppm HCFC - 123. Significant dilution of ambient air by asphyxiants causes air hunger, increased breathing frequency, drowsiness, weakness, and ringing in ears.

PRIMARY ROUTES OF ENTRY - Inhalation

TARGET ORGANS - Lungs

MEDICAL CONDITIONS GENERALLY RECOGNIZED AS BEING AGGRAVATED BY EXPOSURE - No Information

EXPOSURE LIMITS - Not established for HCFC - 123. A manufacturer suggests 10 ppm TWA.

CARCINOGENICITY DATA - Neither Nitrogen nor HCFC - 123 is listed by NIOSH, RTECS, IARC, NTP or OSHA.

EMERGENCY AND FIRST AID PROCEDURES - Remove victim from exposure. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention immediately.

---

### SAFE HANDLING AND USE

---

HYGIENIC PRACTICES - Avoid Breathing Gas

PROTECTIVE MEASURES DURING REPAIR AND MAINTENANCE OF CONTAMINATED EQUIPMENT - N/A

PROCEDURES FOR SPILL OR LEAK CLEANUP - Ventilate Area

WASTE DISPOSAL - Do not puncture or incinerate cylinder. Before discarding cylinder, slowly release contents to a safe exhaust.

STORAGE - Store in a cool, dry, well-ventilated area. Do not exceed 120°F.

---

### CONTROL MEASURES

---

PERSONAL PROTECTIVE EQUIPMENT - Due to the limited amount of gas in the cylinder, and the low release rate employed in instrument calibration, respiratory protection is not indicated under conditions of intended use.

ENGINEERING CONTROLS - Mechanical ventilation is suitable.

WORK PRACTICES - Avoid breathing gas. Use in well-ventilated areas. Follow the calibration procedure detailed in the MSA instruction manual provided with the instrument under calibration.

DATE OF PREPARATION - Rev. 2, June 1999

WARNING: This is a hazardous chemical product. By following the directions and warnings provided with this product, the hazards associated with the use of this product can be greatly reduced but never entirely eliminated. Mine Safety Appliances Company makes no warranties, expressed or implied, with respect to this product and EXPRESSLY DISCLAIMS THE WARRANTY OF MERCHANTABILITY AND ANY WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE. Users assume all risks in handling, using or storing this product.