MSDS: B2349

ITEM: 5A460 - Liquid Rubber 1 Lb ORDER: 0078500691 LP NUMBER: U700931928

MATERIAL SAFETY DA	ATA SHEET (MSDS)
This MSDS should be attached or kept with the remains and safety data sheet - B2349	BSPECTIVE product with which it is associated. ####################################
Associated Grainger Items 5A460	FLASH POINT: >275 DEG. F (135 DEG. C) FLASH POINT METHOD: TAG CLOSED CUP (TCC)
DEVCON(R*)	LOWER EXPLOSIVE LIMIT (LEL): NOT DETERMINED. UPPER EXPLOSIVE LIMIT (UEL): NOT DETERMINED.
SECTION 1: PRODUCT AND COMPANY IDENTIFICATION	EXTINGUISHING MEDIA:
PRODUCT NAME: FLEXANE 80 LIQUID CURING AGENT	USE CARBON DIOXIDE (CO2) OR DRY CHEMICAL WHEN FIGHTING FIRES INVOLVING THIS MATERIAL.
MANUFACTURER NAME: ITW DEVCON	PROTECTIVE EQUIPMENT:
ADDRESS: 30 EMDICOTT STREET DANVERS, MA 01923	AS IN ANY FIRE, WEAR SELF-COMTAINED BREATHING APPARATUS PRESSURE-DEMAND, MSHA/NIOSH (APPROVED OR EQUIVALENT) AND FULL PROTECTIVE GEAR.
MSDS REVISION DATE: 10/10/2006	FIRE FIGHTING INSTRUCTIONS: EVACUATE AREA OF UNPROTECTED PERSONNEL, USE COLD WATER SPRAY TO COOL FIRE
EMERGENCY TELEPHONE NUMBER: (800) 424-9300	EXPOSED CONTAINERS TO MINIMIZE RISK OF RUPTURE. DO NOT ENTER CONFINED FIRE SPACE WITHOUT FULL PROTECTIVE GEAR. IF POSSIBLE, CONTAIN FIRE RUN-OFF WATER.
IN THE US, CALL CHEMTREC: (800) 424-9300	UNSUITABLE MEDIA: WATER OR FOAM MAY CAUSE FROTHING.
HMIS:	SECTION 6: ACCIDENTAL RELEASE MEASURES
HEALTH HAZARD 2* FIRE HAZARD 1 REACTIVITY 0 PERSONAL PROTECTION X	PERSONAL PRECAUTIONS: EVACUATE AREA AND KEEP UNNECESSARY AND UNPROTECTED PERSONNEL FROM ENTERING THE SPILL AREA.
* CHRONIC HEALTH EFFECTS	SPILL CLEANUP MEASURES:
	ABSORB SPILL WITH INERT MATERIAL (E.G., DRY SAND OR EARTH), THEN PLACE IN A CHEMICAL WASTE-CONTAINER. PROVIDE VENTILATION. CLEAN UP SPILLS IMMEDIATELY
SECTION 2: COMPOSITION/INFORMATION ON INGREDIENTS	OBSERVING PRECAUTIONS IN THE PROTECTIVE DOUTEMENT SECTION. AFTER REMOVAL, FLUSH SPILL AREA WITH SOAP AND WATER TO REMOVE TRACE RESIDUE.
CHEMICAL NAME CAS#	AVOID PERSONAL CONTACT AND BREATHING VAPORS OR MISTS. VENTILATE AREA. USE
DIFROPYLENE GLYCOL DIBENZOATE 27138-31-4 60 - 100 BY WEIGHT DIETHYLTOLUENEDIAMINE 68479-98-1 0.1 - 0.1 BY WEIGHT	PROPER PERSONAL PROTECTIVE EQUIPMENT AS LISTED IN SECTION 8.
EPOXIDIZED SOYBEAN OIL 8013-07-8 1 - 5 BY WEIGHT	ENVIRONMENTAL PRECAUTIONS: AVOID RUNOFF INTO STORM SEWERS, DITCHES, AND WATERWAYS.
CARBON BLACK 1333-86-4 0.1 - 1 BY WEIGHT	OTHER PRECAUTIONS: PUMP OR SHOVEL TO STORAGE/SALVAGE VESSELS.
SECTION 3: HAZARDS IDENTIFICATION —	SECTION 7: HANDLING AND STORAGE
EMERGENCY OVERVIEW;	HANDLING: USE WITH ADEQUATE VENTILATION, AVOID BREATHING VAPOR, AEROSOL OR MIST.
WARNING:	STORAGE: STORE IN A COOL, DRY, WELL VENTILATED AREA AWAY FROM SOURCES OF HEAT AND
HARMFUL, IRRITANT.	INCOMPATIBLE MATERIALS. KEEP CONTAINER TIGHTLY CLOSED WHEN NOT IN USE. DO NOT STORE IN REACTIVE METAL CONTAINERS. KEEP AWAY FROM ACIDS, OXIDIZERS.
PRIMARY ROUTES OF EXPOSURE: EYES. SKIN. INHALATION, INGESTION.	HYGIENE PRACTICES: WASH THOROUGHLY AFTER HANDLING.
POTENTIAL HEALTH EFFECTS: EYE CONTACT:	SPECIAL HANDLING PROCEDURES:
CAN CAUSE SEVERE EYE IRRITATION AND BURNS. EYE CONTACT MAY CAUSE PERMANENT DAMAGE OR BLINDNESS.	PROVIDE APPROPRIATE VENTILATION/RESPIRATORY PROTECTION AGAINST DECOMPOSITION PRODUCTS (SEE SECTION 10) DURING WELDING/FLAME CUITING OPERATIONS AND TO PROTECT AGAINST DUST DURING SANDING/GRINDING OF CURED PRODUCT.
SKIN CONTACT: CAUSES SEVERE SKIN IRRITATION. MAY CAUSE PERMANENT SKIN DAMAGE.	SECTION 8: EXPOSURE CONTROLS, PERSONAL PROTECTION
INHALATION: VAPOR OR MIST MAY CAUSE SEVERE RESPIRATORY SYSTEM IRRITATION.	ENGINEERING CONTROLS:
INGESTION: CAUSES IRRITATION, A BURNING SENSATION OF THE MOUTH, THROAT AND GASTROINTESTINAL TRACT AND ABDOMINAL PAIN.	USE APPROPRIATE ENGINEERING CONTROL SUCH AS PROCESS ENCLOSURES, LOCAL EXHAUST VENITILATION, OR OTHER ENGINEERING CONTROLS TO CONTROL ARREPORD LEVELS BELOW RECOMMENDED EXPOSURE LIMITS. GOOD GENERAL VENTILATION SHOULD BE SUFFICIENT TO CONTROL AIRBORNE LEVELS, WHERE SUCH SYSTEMS ARE NOT
CHRONIC HEALTH EFFECTS: PROLOWED SKIN CONTACT MAY LEAD TO BURNING ASSOCIATED WITH SEVERE REDDENING, SWELLING, AND POSSIBLE TISSUE DESTRUCTION	EFFECTIVE WEAR SUITABLE PERSONAL PROTECTIVE EQUIPMENT, WHICH PERFORMS SATISFACTORILY AND MEETS OSHA OR OTHER RECOGNIZED STANDARDS. CONSULT WITH LOCAL PROCEDURES FOR SELECTION, TRAINING, INSPECTION AND MAINTENANCE OF THE PERSONAL PROTECTIVE EQUIPMENT.
SIGNS/SYMPTOMS:	SKIN PROTECTION DESCRIPTION:
OVEREXROSURE MAY CAUSE EYE WATERING OR DISCOMPORT, REDNESS AND SWELLING. TARGET ORGANS: EYES. SKIN. RESPIRATORY SYSTEM. DIGESTIVE SYSTEM.	WEAR APPROPRIATE PROTECTIVE GLOVES AND OTHER PROTECTIVE APPAREL TO PREVENT SKIN CONTACT. CONSULT MANUFACTURER'S DATA FOR PERMEABILITY DATA.
AGGRAVATION OF PRE-EXISTING CONDITIONS: MAY AGGRAVATE PRE-EXISTING RESPIRATORY DISORDERS, ALLERGY, ECZEMA, OR SKIN CONDITIONS.	EYE/FACE PROTECTION: WEAR APPROPRIATE PROTECTIVE GLASSES OR SPLASH GOOGLES AS DESCRIBED BY 29 CFR 1910.133, OSHA EYE AND FACE PROTECTION REGULATION, OR THE EUROPEAN STANDARD EN 166.
SECTION 4: FIRST AID MEASURES	RESPIRATORY PROTECTION: A NICSH APPROVED ATR-PURIFYING RESPIRATOR WITH AN ORGANIC VALOR CAPTRITYS
EYE CONTACT: IMMEDIATELY FIUSH EYES WITH PLENTY OF WATER FOR AT LEAST 15 TO 20 MINUTES. ENSURE ADBOUATE FIUSHING OF THE EYES BY SEPARATING THE EYELIDS WITH FINGERS. GET IMMEDIATE MEDICAL ATTENTION.	OR CANISTER MAY BE PERMISSIBLE UNDER CERTAIN CIRCUMSTANCES WHERE AIRBORNE CONCENTRATIONS ARE EXPECTED TO EXCEED EXPOSURE LIMITS. PROTECTION PROVIDED BY AIR PURIFYING RESPIRATORS IS LIMITED. USE A POSITIVE PRESSURE AIR SUPPLIED RESPIRATOR IF THERE IS ANY POTENTIAL FOR AN UNCONTROLLED RELEASE, EXPOSURE LEVELS ARE NOT KNOWN, OR ANY OTHER CIRCUMSTANCES WHERE AIR
SKIN CONTACT: INMEDIATELY WASH SKIN WITH PLENTY OF SOAP AND WATER FOR 15 TO 20 MINUTES, WHILE REMOVING CONTAMINATED LICITHING AND SHOES. GET MEDICAL ATTENTION IF IRRITATION DEVELOPS OR PERSISTS.	PURIFYING RESPIRATORS MAY NOT PROVIDE ADEQUATE PROTECTION. OTHER PROTECTIVE: FACTLITIES STORING OR UTILIZING THIS MATERIAL SHOULD BE EQUIPPED WITH AN EYEWASH AND A DELUGE SHOWER SAFETY STATION.
INHALATION: IF INHALED, REMOVE TO FRESH AIR. IF NOT BREATHING, GIVE ARTIFICIAL RESPIRATION OR GIVE CXYGEN BY TRAINED PERSONNEL SEEK IMMEDIATE MEDICAL ATTENTION.	CARBON BLACK: GUIDELINE ACGIH: ACGIH TLV-TWA: 3.5 MG/M3
INGESTION: IF SWALLOWED, DO NOT INDUCE VOMITING. CALL A PHYSICIAN OR POISON CONTROL CENTER IMMEDIATELY. NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON.	NOTES: ONLY ESTABLISHED PEL AND TLV VALUES FOR THE INCREDIENTS ARE LISTED BELOW.
SECTION 5: FIRE FIGHTING MEASURES	SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES
FLAMMABLE PROPERTIES: MATERIAL SUPPORTS COMBUSTION.	PHYSICAL STATE/APPEARANCE: LIQUID.

COLOR: MOBILE BLACK.

ODOR: MILD AMMONIA LIKE, BOILING POINT: >450 DEG. F (232.2 DEG. C) MELTING / FREEZING POINT: NOT DETERMINED. SOLUBILITY: NEGLIGIBLE SPECIFIC GRAVITY: 1.08 pH: 7-8 @ 5 PERCENT SOLUTION VAPOR DENSITY: >1 (AIR = 1) VAPOR PRESSURE: <1 MMHg @ 70 DEG. F MOLECULAR FORMULA: MIXTURE MOLECULAR WEIGHT: MIXTURE PERCENT VOLATILE: 0 VOC DATA: 0 G/L PERCENT SOLIDS BY WEIGHT: 100 - SECTION 10: STABILITY AND REACTIVITY CHEMICAL STABILITY: STABLE UNDER NORMAL TEMPERATURES AND PRESSURES. CONDITIONS TO AVOID: EXTREME HEAT, SPARKS, AND OPEN FLAME. INCOMPATIBLE MATERIALS, OXIDIZERS AND OXIDIZING CONDITIONS. INCOMPATIBILITIES WITH OTHER MATERIALS:
OXIDIZERS, ACIDS, AND CHLORINATED ORGANIC COMPOUNDS. REACTIVE METALS (E.G. SODIUM, CALCIUM, LINC). SODIUM/CALCIUM HYPOCHLORITE. NITROUS ACID/OXIDE,
NITRITES. PEROXIDES. MATERIALS REACTIVE WITH HYDROXYL COMPOUNDS. HAZARDOUS POLYMERIZATION: NOT REPORTED - SECTION 11: TOXICOLOGICAL INFORMATION -DIETHYLTOLUENEDIAMINE: INGESTION EFFECTS: ORAL - RAT LD50: 472 MG/KG - (SENSE ORGANS AND SPECIAL SENSES (EYE) - LACRIMATION ORAL -SONVOLENCE (GENERAL DEPRESSED ACTIVITY) MUSCULOSKELETAL - OTHER CHANGES) EPOXIDIZED SOYBEAN OIL: SKIN EFFECTS: SKIN - RABBIT OPEN IRRITATION TEST: 500 MG - (MILD) (RTECS) SKIN - RABBIT LD50: >20 ML/KG - (DETAILS OF TOXIC EFFECTS NOT REPORTED OTHER THAN LETHAL DOSE VALUE) (RTECS) INGESTION EFFECTS: ORAL - RAT LD50: 22500 (MICRO)L/KG - (DETAILS OF TOXIC EFFECTS NOT REPORTED OTHER THAN LETHAL DOSE VALUE) (RTECS) CARBON BLACK: SKIN EFFECTS SKIN - RABBIT LD50: $>\!\!3$ GM/KG - (DETAILS OF TOXIC EFFECTS NOT REPORTED OTHER THAN LETHAL DOSE VALUE) (RTECS) INHALATION EFFECTS:
INHALATION - RAT TCLO - LOWEST PUBLISHED TOXIC CONCENTRATION:
7 MS/M3 - (LUNGS, THORAX, OR RESPIRATION - OTHER CHANGES BIOCHEMICAL METABOLISM (INTERMEDIARY) - EFFECT ON INFLAMMATION OR MEDIATION OF INFLAMMATION) (RTECS) ORAL - RAT LD50: >15400 MG/KG - (ORAL - SOMNOLENCE (GENERAL DEPRESSED ACTIVITY)) (RTECS) CARCINOGENICITY: GROUP 2B: POSSIBLY CARCINOGENIC TO HUMANS - SECTION 12: ECOLOGICAL INFORMATION ECCTOXICITY: NO ECOTOXICITY DATA WAS FOUND FOR THE PRODUCT. ENVIRONMENTAL FATE: NO ENVIRONMENTAL INFORMATION FOUND FOR THIS PRODUCT. - SECTION 13: DISPOSAL CONSIDERATIONS WASTE DISPOSAL:
CONSULT WITH THE US EPA GUIDELINES LISTED IN 40 CFR PART 261.3 FOR THE
CLASSIFICATIONS OF HAZARDOUS WASTE PRIOR TO DISPOSAL. FURTHERMORE, CONSULT
WITH YOUR STATE AND LOCAL WASTE REQUIREMENTS OR GUIDELINES, IF APPLICABLE,
TO ENSURE COMPLIANCE, ARRANGE DISPOSAL IN ACCORDANCE TO THE EPA AND/OR STATE
AND LOCAL GUIDELINES.

- SECTION 14: TRANSPORT INFORMATION

RCRA NUMBER: NONE

DOT SHIPPING NAME: NON REGULATED.

DOT UN NUMBER: NOT APPLICABLE.

DOT HAZARD CLASS: NOT APPLICABLE.

DOT PACKING GROUP: NOT APPLICABLE.

LISTED IN THE STATE OF MASSACHUSETTS HAZARDOUS SUBSTANCE LIST. LISTED IN THE PENNSYLVANIA STATE HAZARDOUS SUBSTANCES LIST. CANADIAN REGULATIONS: WHMIS HAZARD CLASS(ES): D2B, D2A ALL COMPONENTS OF THIS PRODUCT ARE ON THE CANADIAN DOMESTIC SUBSTANCES LIST. - SECTION 16: ADDITIONAL INFORMATION -HMIS HEALTH HAZARD HMIS FIRE HAZARD HMIS REACTIVITY 1. HMIS PERSONAL PROTECTION X MSDS REVISION DATE: 10/10/2006 DISCLAIMER:
THIS HEALTH AND SAFETY INFORMATION IS CORRECT TO THE BEST OF OUR KNOWLEDGE AND BELLEF AT THE DATE OF ITS FUBLICATION BUT WE CANNOT ACCEPT LIABILITY FOR ANY LOSS, INJURY OR DAMAGE WHICH MAY RESULT FROM ITS USE. THE INFORMATION GIVEN IN THE DATA SHEET IS DESIGNED ONLY AS A GUIDANCE FOR SAFE HABILING, STORAGE AND THE USE OF THE SUBSTRANCE. IT IS NOT A SPECIFICATION NOR DOES IT GUARANTEE ANY SPECIFIC PROPERTIES. ALL CHEMICALS SHOULD BE HANDLED ONLY BY COMPETENT PERSONNEL, WITHIN A CONTROLLED ENVIRONMENT. COPYRIGHT (C) 1996-2007 ACTIO SOFTWARE CORPORATION. ALL RIGHTS RESERVED.

SECTION 15: REGULATORY INFORMATION

WHMIS PICTOGRAMS:

TSCA INVENTORY STATUS: LISTED

CARBON BLACK ::

D2 - MATERIALS CAUSING OTHER TOXIC EFFECTS